

TECHNICAL FACT SHEET

SIMPLICITY 6

Max Projection	3.5m
Max Between Posts	3m
Gutter Infill Channel	Always Included
Max Inset of Posts	500mm (either end)
Max Height at the Front	3m
Min Pitch	2.5 ° (10 ° for self-cleaning)
Max Pitch	22.5 °
Roof Panel Type	6mm toughened glass
Max Space Between Bars	600mm
Length	Unlimited
Glass Options	Clear, Clear Self-Cleaning, Grey Tinted, Bronze Tinted
Glass Thickness	6mm
Post Options	Standard 70mm x 75mm Square 70mm x 70mm Xtra post 100mm x 70mm
Lighting Options Available	RGB Lighting in the Main Bars and Gutter
Upgrades	Victorian gallows brackets and base castings, (70mm x 75mm posts only) heaters, glass rooms, fixed panels.
Wall Plate Height	111mm
Gutter Support Kit	100mm x 70mm Box Section to extend the maximum between posts to 4m. Please note: Reduces front height by 70mm

SIMPLICITY 16

Max Projection	4m
Max Between Posts	3m
Gutter Infill Channel	Optional Extra
Max height at the front	3m
Max Inset of Posts	500mm (either end)
Min Pitch	2.5 °
Max Pitch	22.5 °
Roof Panel Type	16mm Multi-Wall Poly
Max Space Between Bars	1000mm (up to 3m projection) 700mm, (over 3m projection) & 500mm (over 3.5m projection)
Length	Unlimited
Poly Options	Clear, Bronze, Opal and Grey Heat Guard
Poly Thickness	16mm
Post Options	Standard 70mm x 75mm Square 70mm x 70mm Xtra post 100mm x 70mm
Lighting Options Available	Gutter Only
Upgrades	Victorian Gallows Brackets and Base Castings, (70mm x 75mm Posts Only) Heaters, Glass Rooms, Fixed Panels.
Wall Plate Height	111mm
Gutter Support Kit	100mm x 70mm Box Section to Extend the Maximum Between Posts to 4m Please note: Reduces Front Height by 70mm

TECHNICAL FACT SHEET

SIMPLICITY XTRA

Max Projection	4m
Max Between Posts	4m
Max Inset of Posts	500mm (either end)
Max height at the front	3m
Min Pitch	2.5 °
Max Pitch	22.25 ° up to 3750m projection - up to 4m Refer to Pitch Chart
Roof Panel Type	6mm Toughened Glass
Max Space Between Bars	600mm
Length	Unlimited
Glass Options	Clear, Clear Self-Cleaning, Grey Tinted, Bronze Tinted
Glass Thickness	6mm
Post Options	Standard 70mm x 75mm Square 70mm x 70mm Xtra post 100mm x 70mm
Lighting Options Available	Spot lights in Bars Only
Upgrades	Victorian Gallows Brackets and Base Castings, (75mm x 70mm Posts Only) Heaters, Glass Rooms, Fixed Panels.
Wall Plate Height	147mm

SIMPLICITY 35

Max Projection	6m
Max Between Posts	3.5m
Max Inset of Posts	500mm (either end)
Max height at the front	3m
Min pitch	2.5 °
Max pitch	45 °
Roof panel type	35mm Multi-Wall Poly
Max Space Between Bars	1250mm (up to 4m projection), 1000mm (up to 6m projection) 600mm up
Length	Unlimited
Poly Options	Clear, Bronze, Opal, Grey/Opal Heatguard
Poly Thickness	35mm
Post Options	80mm x 80mm
Lighting Options Available	RGB Lighting in the Main Bars & Gutter
Upgrades	Heaters
Wall Plate Height	124mm

TECHNICAL FACT SHEET

ALFRESCO CONTEMPORARY

Max Projection	6m
Max Between Posts	6m
Max Inset of Posts	500mm (either end)
Max height at the front	3m
Min Pitch	5 °
Max Pitch	45 °
Roof Panel Type	8mm Toughened Glass
Max Space Between Bars	800mm
Max glass length	3m
Length	Unlimited
Glass Options	Clear and Grey Glass
Glass Thickness	8mm
Post Options	150mm x 150mm
Lighting Options Available	RGB Lighting in the Main Bars Only
Upgrades	Heaters, Glass Room, Glass Doors, Fixed Panels
Wall Plate Height	160mm

SIMPLICITY FREE

Max Projection	4m
Max Between Posts	4m
Max height	3m
Min Pitch	Varies dependent on projection
Max Pitch	Fixed, see above
Roof Panel Type	6mm Toughened Glass
Max Space Between Bars	600mm
Length	Unlimited
Glass Options	Clear, Grey Tinted, Bronze Tinted
Glass Thickness	6mm
Post Options	Square 150mm x 150mm
Lighting Options Available	Spot lights in Bars Only
Upgrades	Glass Room, Heaters, Fixed Panels
Wall Plate Height/Ring Beam	305mm

TECHNICAL FACT SHEET

A-FENCE

Max Between Posts	6ft, 1820mm
Max Post Height	6ft, 1820mm
Min Between Posts	N/A
Min Post Height	180mm
Panel Sizes	50mm, 100mm, 150mm
Panel Width	19mm
Max Panel Spacing	None
Max Panel Length	180cm, 1800mm
Colours	RAL 7016 Anthracite Grey, RAL 9005 Jet Black